

SAFETY DATA SHEET

MOTAQUIP SPRAY GREASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	MOTAQUIP SPRAY GREASE
Product number	VOL411
Internal identification	15005

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	All-purpose industrial and automotive grease.
Uses advised against	This product is not recommended for any industrial, professional or consumer use other than the identified uses stated above.

1.3. Details of the supplier of the safety data sheet

Supplier	MOTAQUIP LIMITED Unit B1, Luton Enterprise Park, Sundon Park Road, Luton Bedfordshire LU3 3GU
----------	--

1.4. Emergency telephone number

Emergency telephone	Tel:
---------------------	------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315
Environmental hazards	Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) F+;R12. R52/53.

Human health	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Environmental	The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Physicochemical	Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word Danger

MOTAQUIP SPRAY GREASE

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H315 Causes skin irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container in accordance with national regulations. P102 Keep out of reach of children.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTANE		10-30%
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32-XXXX
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12	
NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT		10-30%
CAS number: 64742-49-0	REACH registration number: 01-2119475514-35-XXXX	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC.		10-30%
CAS number: 64742-52-5	EC number: 265-155-0	REACH registration number: 01-2119467170-45-XXXX
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -	

MOTAQUIP SPRAY GREASE

SOLVENT REFINED LIGHT PARAFFINIC DISTILLATE			10-30%
CAS number: 64742-54-7	EC number: 265-157-1	REACH registration number: 01-2119484627-25-XXXX	
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -		

LITHIUM 12-HYDROXYSTEARATE			1-5%
CAS number: 7620-77-1	EC number: 231-536-5		
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Repeated exposure to high levels may affect the central nervous system. Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Due to the physical nature of this material it is unlikely that swallowing will occur. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

MOTAQUIP SPRAY GREASE

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Nitrogen oxides.

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of spray mist and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid contact with skin or inhalation of spillage, dust or vapour. Absorb in vermiculite, dry sand or earth and place into containers. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Use non sparking handtools and explosion-proof electric equipment. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

MOTAQUIP SPRAY GREASE

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

Carc

The carcinogenic classification only applies if Butane contains more than 0.1% of buta-1,3-diene.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

No exposure limit value known.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC.

No exposure limit value known.

Italy, Portugal, USA: ACGIH TWA: 5mg/m³; STEL: 10mg/m³

SOLVENT REFINED LIGHT PARAFFINIC DISTILLATE

No exposure limit value known.

LITHIUM 12-HYDROXYSTEARATE

No exposure limit value known.

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

Ingredient comments WEL = Workplace Exposure Limits

BUTANE (CAS: 106-97-8)

DNEL No DNEL available.

PNEC No PNEC available.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT (CAS: 64742-49-0)

DNEL Industry - Dermal; Long term systemic effects: >300 mg/kg/day
 Industry - Inhalation; Long term systemic effects: >2035 mg/kg/day
 Consumer - Dermal; Long term systemic effects: >699 mg/kg/day
 Consumer - Oral; Long term systemic effects: >699 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: >608 mg/m³

PNEC No PNEC available.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC. (CAS: 64742-52-5)

DNEL No DNEL available.

PNEC The substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods for deriving the PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substance.

SOLVENT REFINED LIGHT PARAFFINIC DISTILLATE (CAS: 64742-54-7)

DNEL No DNEL available.

PNEC No PNEC available.

MOTAQUIP SPRAY GREASE

ISOBUTANE (CAS: 75-28-5)

DNEL No DNEL available.

PNEC No PNEC available.

LITHIUM 12-HYDROXYSTEARATE (CAS: 7620-77-1)

DNEL Workers, General population - Dermal; Long term systemic effects: 41 mg/kg bw/day

Workers - Dermal; Long term local effects: 0.172 mg/cm²

General population - Dermal; Long term local effects: 0.086 mg/cm²

General population - Oral; Long term systemic effects: 41 mg/kg bw/day

Workers, General population - Dermal; Short term Acute: 41 mg/kg bw/day

General population - Oral; Short term Acute: 41 mg/kg bw/day

PNEC

- Fresh water; 0.1 mg/l
- Marine water; 0.01 mg/l
- Intermittent release; 1 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

None required when product is used as instructed. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

No specific precautions due to the small quantities handled. In case of intensive contact, wear protective gloves (EN 374). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. protective gloves shall be replaced immediately when physically damaged or worn. Appropriate Material - Butyl, Material Thickness - 0.6 to 0.8mm, Breakthrough Time - 8Hrs

Other skin and body protection

Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Hygiene measures

Do not smoke in work area. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

MOTAQUIP SPRAY GREASE

Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
--	--

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Amber.
Odour	Characteristic. Hydrocarbons. Solvent.
Flash point	-74°C (Propellant)°C CC (Closed cup).
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8% (Propellant) Upper flammable/explosive limit: 10% (Propellant)
Solubility(ies)	Insoluble in water. Very soluble in the following materials: Oil

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Will not polymerise.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Strong alkalis. Strong oxidising agents.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information	To the best of our knowledge the chemical, physical and toxicological properties have not been thoroughly investigated.
Inhalation	May cause respiratory system irritation. Prolonged inhalation of high concentrations may damage respiratory system. Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Swallowing concentrated chemical may cause severe internal injury. May cause discomfort if swallowed. May cause stomach pain or vomiting.

MOTAQUIP SPRAY GREASE

Skin contact	Repeated exposure may cause skin dryness or cracking. Repeated or prolonged exposure may lead to irritation and dermatitis. Irritating to skin.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Route of entry	Inhalation Skin and/or eye contact

Toxicological information on ingredients.

BUTANE

Acute toxicity - oral

Notes (oral LD₅₀) No information available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No information available.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 658.0

Species Rat

ATE inhalation (vapours mg/l) 658.0

Skin corrosion/irritation

Animal data Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation No known effects from this product.

Skin sensitisation

Skin sensitisation No known effects from this product.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity No information available.

IARC carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

Reproductive toxicity

Reproductive toxicity - fertility No evidence of reproductive toxicity in animal studies.

Reproductive toxicity - development This substance has no evidence of toxicity to reproduction.

MOTAQUIP SPRAY GREASE

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard No data available.

Inhalation

In low concentrations may cause narcotic effects, dizziness, headache, nausea, loss of co-ordination and irregular cardiac activity. In high concentrations may cause loss of mobility/consciousness and it may cause asphyxiation.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat Rat

ATE oral (mg/kg) 5,841.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,920.0

Species Rat Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 23.5

Species Rat

ATE inhalation (vapours mg/l) 23.5

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not classified. May cause slight transient irritation.

Skin sensitisation

Skin sensitisation Not considered to be a skin sensitizer

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

MOTAQUIP SPRAY GREASE

Carcinogenicity	The current toxicological knowledge allows to not classify the product as a carcinogen.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
Reproductive toxicity - development	No evidence of reproductive toxicity in animal studies.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No known effects based on information supplied.
Target organs	Central nervous system
<u>Aspiration hazard</u>	
Aspiration hazard	The fluid can enter the lungs and cause damage (chemical pneumonitis, possibly fatal).
.	
Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Avoid vomiting and stomach flushing because of the risk of aspiration. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Irritating to skin.
Eye contact	May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Ecological information on ingredients.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Ecological information on ingredients.

BUTANE

Acute toxicity - fish	LC ₅₀ , 96 hours: 24.11 mg/l, Fish
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 14.22 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 7.71 mg/l, Freshwater algae

MOTAQUIP SPRAY GREASE

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Acute toxicity - fish	LL ₅₀ , 96 hours: 11.4 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: 3 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 10 mg/l, Freshwater algae
Chronic toxicity - fish early life stage	NOEC, 28 days, 28 days: 1.534 mg/l, Onchorhynchus mykiss (Rainbow trout)
Chronic toxicity - aquatic invertebrates	NOEC, 21 days, 21 days: 1 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be slowly biodegradable. Volatile substances are degraded in the atmosphere within a few days. The product is degraded completely by photochemical oxidation.

Ecological information on ingredients.

BUTANE

Biodegradation The substance is readily biodegradable.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Persistence and degradability The substance is readily biodegradable.

Biodegradation - Degradation (%) 98: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential May accumulate in soil and water systems.

Ecological information on ingredients.

BUTANE

Bioaccumulative potential The product is not bioaccumulating.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Bioaccumulative potential Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

12.4. Mobility in soil

Mobility The product contains substances which are insoluble in water and which may spread on water surfaces.

Ecological information on ingredients.

BUTANE

MOTAQUIP SPRAY GREASE

Mobility No data available.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Mobility Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

BUTANE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

NAPHTHA (PETROLEUM), HYDROTREATED, LIGHT

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

MOTAQUIP SPRAY GREASE

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Pollution (Special Waste) Regulations 1980 (as amended).
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Dangerous Substances Directive 67/548/EEC.
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.
CHIP for everyone HSG228.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by HS&E Manager.

MOTAQUIP SPRAY GREASE

Revision date	24/11/2014
Revision	5
Supersedes date	28/05/2013
SDS status	Approved.
Risk phrases in full	R11 Highly flammable. R12 Extremely flammable. R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.